

Flexilight Top is a silicone tape with a width of 15 mm offering a perfectly homogeneous flow of a CRI 96+

SPECIFICATIONS

Voltage	24VDC
Power	20W/m
LED quantity per meter	168 LEDs / m
LED type	SMD 2835
Current regulator	Embeddeb
Cutting	Monochrome : 50mm
	Twin White : 72mm
IP rate	IP65 / IP67 on request
Minimum radius	200mm

DIMENSIONS

Width	15 mm
Thickness	15 mm
Length	up to 7,5 m for longer lengths, contact us.

K - IRC - lm/m.

FOS411	2300K / 96 / 715lm
FOS415	2700K / 96 / 803lm
FOS421	3000K / 96 / 858lm
FOS425	3500K / 82 / 880lm
FOS431	4000K / 82 / 902lm
FOS401	2300K + 4000K/ 96 / 809lm
FOS406	2700K + 4000K/ 96 / 853lm
FOS408	2300k + 3000k / 96 / 787lm

CONNECTION

FOS400-SEP	Connection in the extension
FOS400-SLB	Right side connection
FOS400-SLH	Left side connection
FOS400-SED	Opposite connection to light
FOS047-CLIP	Spring steel clip

WARRANTY

3 years under normal conditions of use

