

Tinyspot Hirondele

Tinyspot is a range of three 150 and 500 lumen spots for event and museum applications. On-site adjustments are easy thanks to many types of filters and low luminance magnet accessories as well as its 24VDC power on 3.5 jack. Powering systems on masts or tracks allow easy integration.

ELECTRICAL FEATURES

Voltage	24VDC
Power	5W
Régulator	Embedded
Control	1-10V, DALI, DMX....
Class	III

DIMENSIONS

Length	43mm
Diameter	33mm
Finish	Aluminum, black, white

PHOTOMETRIC FEATURES

IRC / TM30	96/98, rf94
SDCM	2
K / lumens output	2400K / 330lm
	2700k / 390lm
	3000K / 400lm
	3500K / 420lm
	4000K / 440lm
	3500K UV / 400lm
	4000K UV / 420lm
	5500K UV / 440lm

OPTICAL FEATURES

Material	PMMA
Angles	15°
Additional optics	5°, 10°, 20°, 30°, 60°, 90°, 1°x 90°, 2° x 70°, Bat wing 30° x 80°
Beam direction	H : 360° / V : +/-90°

ACCESSORIES

Cap grey

Louver long grey

Louver short grey

Filter holder grey

CERTIFICATION & WARRANTY

5 years under normal conditions of use

CE & UL

IP20



Tinyspot Hirondelle

Aluminum finish

SLD521	Spot Hirondelle 2400K Aluminium
SLD522	Spot Hirondelle 2700K Aluminium
SLD523	Spot Hirondelle 3000K Aluminium
SLD524	Spot Hirondelle 3500K Aluminium
SLD525	Spot Hirondelle 4000K Aluminium
SLD526	Spot Hirondelle 3500K UV Aluminium
SLD527	Spot Hirondelle 4000K UV Aluminium
SLD528	Spot Hirondelle 5500K UV Aluminium

Black finish

SLD531	Spot Hirondelle 2400K black
SLD532	Spot Hirondelle 2700K black
SLD533	Spot Hirondelle 3000K black
SLD534	Spot Hirondelle 3500K black
SLD535	Spot Hirondelle 4000K black
SLD536	Spot Hirondelle 3500K UV black
SLD537	Spot Hirondelle 4000K UV black
SLD538	Spot Hirondelle 5500K UV black

White finish

SLD541	Spot Hirondelle 2400K white
SLD542	Spot Hirondelle 2700K white
SLD543	Spot Hirondelle 3000K white
SLD544	Spot Hirondelle 3500K white
SLD545	Spot Hirondelle 4000K white
SLD546	Spot Hirondelle 3500K UV white
SLD547	Spot Hirondelle 4000K UV white
SLD548	Spot Hirondelle 5500K UV white

Accessories

Grey finish

CSC521	Cap grey
CSL521	Louver long grey
CSM521	Louver short grey
CSP520	Filter holder grey

Black finish

CSC551	Cap black
CSL551	Louver long black
CSM551	Louver short black
CSP550	Filter holder black

White finish

CSC541	Cap white
CSL541	Louver long white
CSM541	Louver short white
CSP540	Filter holder white

Optical filters

Grey finish

SFI521	Filter 5° grey
SFI522	Filter 10° grey
SFI525	Filter 20° grey
SFI524	Filter 30° grey
SFI525	Filter 60° grey
SFI526	Filter 90° grey
SFI527	Filter 1° x 90° grey
SFI528	Filter 2° x 90° grey
SFI529	Bat Wings 30° x 80° grey

Black finish

SFI551	Filter 5° black
SFI552	Filter 10° black
SFI555	Filter 20° black
SFI554	Filter 30° black
SFI555	Filter 60° black
SFI556	Filter 90° black
SFI557	Filter 1° x 90° black
SFI558	Filter 2° x 90° black
SFI559	Bat Wings 30° x 80° black

White finish

SFI551	Filter 5° white
SFI552	Filter 10° white
SFI555	Filter 20° white
SFI554	Filter 30° white
SFI555	Filter 60° white
SFI556	Filter 90° white
SFI557	Filter 1° x 90° white
SFI558	Filter 2° x 90° white
SFI559	Bat Wings 30° x 80° white

Masts with jack 3.5 connector

Masts from 26 to 500 mm equipped with jack connector 3.5, bases to be fixed on surface or to be integrated.

Grey finish

SMD121	Mast 26 mm grey
SMD122	Mast 50 mm grey
SMD123	Mast 100 mm grey
SMD124	Mast 150 mm grey
SMD125	Mast 200 mm grey
SMD126	Mast 250 mm grey
SMD127	Mast 300 mm grey
SMD128	Mast 350 mm grey
SMD129	Mast 400 mm grey
SMD221	Mast 450 mm grey
SMD222	Mast 500 mm grey

Black finish

SMD131	Mast 26 mm black
SMD132	Mast 50 mm black
SMD133	Mast 100 mm black
SMD134	Mast 150 mm black
SMD135	Mast 200 mm black
SMD136	Mast 250 mm black
SMD137	Mast 300 mm black
SMD138	Mast 350 mm black
SMD139	Mast 400 mm black
SMD231	Mast 450 mm black
SMD232	Mast 500 mm black

White finish

SMD141	Mast 26 mm white
SMD142	Mast 50 mm white
SMD143	Mast 100 mm white
SMD144	Mast 150 mm white
SMD145	Mast 200 mm white
SMD146	Mast 250 mm white
SMD147	Mast 300 mm white
SMD148	Mast 350 mm white
SMD149	Mast 400 mm white
SMD241	Mast 450 mm white
SMD242	Mast 500 mm white

INTEGRATION BASE

SSUI21	Small socket to integrate grey
SSUI31	Small socket to integrate black
SSUI41	Small socket to integrate white

SURFACE BASE

SSU321	Large socket grey
SSU331	Large socket black
SSU441	Large socket white

Power track

24VDC rails with 3.5 jack base every 4 cm for spotlights and connectors at each end to connect several rails together to form lengths up to 12 meters and 250W.

DIMENSIONS

16 mm x 16 mm

Grey finish

SRS121	Power track 80 mm grey
SRS122	Power track 200 mm grey
SRS123	Power track 600 mm grey

Grey finish

SRS131	Power track 80 mm black
SRS132	Power track 200 mm black
SRS133	Power track 600 mm black

Grey finish

SRS141	Power track 80 mm white
SRS142	Power track 200 mm white
SRS143	Power track 600 mm white

VERTICAL TRACK

Grey finish

SRV121	Vertical track 80 mm grey
SRV122	Vertical track 200 mm grey
SRV123	Vertical track 600 mm grey

Grey finish

SRV131	Vertical track 80 mm black
SRV132	Vertical track 200 mm black
SRV133	Vertical track 600 mm black

Grey finish

SRV141	Vertical track 80 mm white
SRV142	Vertical track 200 mm white
SRV143	Vertical track 600 mm white

CONNECTEURS

SSP010	Kit de 2 contacts d'interconnexion, courant maximum 10A
SSP221	Câble d'alimentation et connecteur, courant maximum 10A, gris
SSP231	Câble d'alimentation et connecteur, courant maximum 10A, noir
SSP241	Câble d'alimentation et connecteur, courant maximum 10A, blanc