

Tinyspot is a range of three 150 and 500 lumen spots for event and museum applications. On-site adjustments are easy thanks to many types of filters and low luminance magnet accessories as well as its 24VDC power on 3.5 jack. Powering systems on masts or tracks allow easy integration.

## ELECTRICAL FEATURES

Voltage	24VDC
Power	2.4W
Régulateur	Embedded
Control	1-10V, DALI, DMX....
Class	III

## DIMENSIONS

Length	40mm
Diamètre	19mm
Finish	Black

## PHOTOMETRIC FEATURES

IRC / TM30	96/98, rf94
SDCM	2
K / output lumens	2700K / 140lm
	3000K / 150lm
	3500K / 170lm
	4000K / 180lm

## OPTICAL FEATURES

Material	Quartz optical group
Angles	Adjustable from 6° to 30°
Additional optics	5°, 10°, 20°, 1°x 90°
Beam direction	H : 360° / V : +/-90°

## ARTICLE CODE

SLD432	Spot Colibri HD 2700K black
SLD433	Spot Colibri HD 3000K black
SLD434	Spot Colibri HD 3500K black
SLD435	Spot Colibri HD 4000K black

## ADDITIONAL OPTICS

SFI431	Filter 5° black
SFI432	Filter 10° black
SFI433	Filter 20° black
SFI437	Filter 1° x 90° black

## CERTIFICATION & WARRANTY

5 years under normal conditions of use
CE
IP20



## Masts with jack 3.5 connector

Masts from 26 to 500 mm equipped with jack connector 3.5, bases to be fixed on surface or to be integrated.

### Grey finish

SMD121	Mast 26 mm grey
SMD122	Mast 50 mm grey
SMD123	Mast 100 mm grey
SMD124	Mast 150 mm grey
SMD125	Mast 200 mm grey
SMD126	Mast 250 mm grey
SMD127	Mast 300 mm grey
SMD128	Mast 350 mm grey
SMD129	Mast 400 mm grey
SMD221	Mast 450 mm grey
SMD222	Mast 500 mm grey

### Black finish

SMD131	Mast 26 mm black
SMD132	Mast 50 mm black
SMD133	Mast 100 mm black
SMD134	Mast 150 mm black
SMD135	Mast 200 mm black
SMD136	Mast 250 mm black
SMD137	Mast 300 mm black
SMD138	Mast 350 mm black
SMD139	Mast 400 mm black
SMD231	Mast 450 mm black
SMD232	Mast 500 mm black

### White finish

SMD141	Mast 26 mm white
SMD142	Mast 50 mm white
SMD143	Mast 100 mm white
SMD144	Mast 150 mm white
SMD145	Mast 200 mm white
SMD146	Mast 250 mm white
SMD147	Mast 300 mm white
SMD148	Mast 350 mm white
SMD149	Mast 400 mm white
SMD241	Mast 450 mm white
SMD242	Mast 500 mm white

### INTEGRATION BASE

SSUI21	Small socket to integrate grey
SSUI31	Small socket to integrate black
SSUI41	Small socket to integrate white

## SURFACE BASE

SSU321	Large socket grey
SSU331	Large socket black
SSU441	Large socket white

## Power track

24VDC rails with 3.5 jack base every 4 cm for spotlights and connectors at each end to connect several rails together to form lengths up to 12 meters and 250W.

### DIMENSIONS

16 mm x 16 mm

#### Grey finish

SRS121	Power track 80 mm grey
SRS122	Power track 200 mm grey
SRS123	Power track 600 mm grey

#### Grey finish

SRS131	Power track 80 mm black
SRS132	Power track 200 mm black
SRS133	Power track 600 mm black

#### Grey finish

SRS141	Power track 80 mm white
SRS142	Power track 200 mm white
SRS143	Power track 600 mm white

## VERTICAL TRACK

#### Grey finish

SRV121	Vertical track 80 mm grey
SRV122	Vertical track 200 mm grey
SRV123	Vertical track 600 mm grey

#### Grey finish

SRV131	Vertical track 80 mm black
SRV132	Vertical track 200 mm black
SRV133	Vertical track 600 mm black

#### Grey finish

SRV141	Vertical track 80 mm white
SRV142	Vertical track 200 mm white
SRV143	Vertical track 600 mm white

## CONNECTORS

SSP010	Kit of 2 interconnecting contacts, maximum current 10A
SSP221	Power cable and connector, maximum current 10A, grey
SSP231	Power cable and connector, maximum current 10A, black
SSP241	Power cable and connector, maximum current 10A, white